

Perforated Leather Tester

Single station abrasion (fiber fluff) tester designed to perform tests on materials in accordance with Toyota Specification TIS 01208-00F21

Used for evaluating a leather sample's ability to resist abrading. The cycle speed is 70 CPM (adjustable) with a 20 mm operating stroke.

It includes a blank polished stainless steel oscillating table (double stick tape attachment), a removable (for weight verification) aluminum 95 mm sample disc that weighs 0.5 Kg (double stick tape attachment) and an overhead pass-through sample disc retaining system.

The control system includes a programmable cycle counter with automatic stop.



SDL ATLAS LLC
3934 Airway Drive
Rock Hill, SC 29732-9200, USA
Telephone: +1 803 329 2110
Facsimile: +1 803 329 2133
Website: www.sdlatlas.com

SDL ATLAS LTD.
1/F (South-East) & 2F, Shenjian Mansion,
Central District (West), Hi-Tech Park,
Nanshan, Shenzhen, 518057, P.R.C.
Telephone: +86 (755) 2671 1168
Facsimile: +86 (755) 2671 1337
Website: www.sdlatlas.com

SDL ATLAS LTD.
3J, Garment Centre, 576 Castle Peak Road,
Kowloon, Hong Kong.
Telephone: (852) 3443 4888
Facsimile: (852) 3443 4999
Website: www.sdlatlas.com